

# Plus $\alpha$ Attachments

Selecting from among these designs will improve overall design efficiency for your application.



## Magnetic Attachment (Attachment Type: MG)

A magnet mounted on the attachment holds conveyed objects. Can be used for conveyance on a slope.

- Two types of magnets are available.
- The dimensions shown in this catalog are nominal dimensions and may differ from actual dimensions.



## Rubber Attachment (Attachment Type: RSG)

A layer of rubber is bonded to the attachment. The elasticity of the rubber allows objects to be conveyed between chains.

Note: Specifications for the rubber material will be determined in consultation with the customer.

### Attachment Dimensions

Tsubaki Chain No.	No. of Strands	Pitch P	Roller Dia. $\Phi R$	Width Between Inner Link Plates W	Transverse Pitch C	Pin		Plate		Attachment				
						Dia. $\Phi D$	Length L	Width H	Thickness T	N	S	A	B	$\alpha$
RS40	1	12.70	7.92	7.95	—	3.97	20.0	12.0	1.5	24.4	9.0	4.0	13.0	30
RS40-2	2	12.70	7.92	7.95	14.4	3.97	34.6	12.0	1.5	24.4	9.0	4.0	13.0	30
RS40-3	3	12.70	7.92	7.95	14.4	3.97	48.8	12.0	1.5	24.4	9.0	6.0	15.0	0
RS50-2	2	15.875	10.16	9.53	18.1	5.09	42.0	15.0	2.0	28.8	13.0	10.0	23.0	20
RS60	1	19.05	11.91	12.7	—	5.96	29.5	18.1	2.4	34.6	13.0	10.0	23.0	0
RS60-2	2	19.05	11.91	12.7	22.8	5.96	52.4	18.1	2.4	34.6	13.0	10.0	23.0	20

Note: Dimensions L are all calculated as both ends of the pin being CL secured.

The dimensions shown in this catalog are nominal dimensions and may differ from actual dimensions.

Standard Small Size Conveyor Chain

Special Small Size Conveyor Chain

Lube Free Small Size Conveyor Chain

Corrosion Resistant Small Size Conveyor Chain

Plus  $\alpha$  Small Size Conveyor Chain

High Precision Conveyor Chain

Engineering Manual